

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

圆柱形锂离子电池产品规格表/ Cylindrical Li-ion battery product specification

No.	Series	IEC Model	Capacity (mAh)	Diameter (±0.2mm)	Height (±0.5mm)	Approx: Weight (g)	IR (mΩ)	Nominal Voltage (V)	The maximum discharge rate	Remark
1	3.2V	IFR10440	200	10.0	43.0	9.0	120	3.2	2C	
2		IFR14430	500	13.9	42.5	15.0	110	3.2	2C	
3		IFR14500	650	13.9	48.5	18.0	100	3.2	2C	
4		IFR14650	950	13.9	65.0	24.0	100	3.2	2C	
5		IFR18500	1100	18.0	49.5	31.0	80	3.2	2C	
6		IFR18650	1500	18.0	65.0	42.0	70	3.2	2C	
7		IFR22430	1000	22.0	42.5	42.0	40	3.2	2C	
8		IFR22650	3000	22.0	65.0	60.0	30	3.2	2C	
9		IFR26650	3200	26.0	65.0	85.0	30	3.2	2C	
10		IFR18650	1100	18.0	65.0	40.0	30	3.2	15C	High rate
11		IFR26650	2200	26.0	65.0	90.0	20	3.2	15C	
12		IFR14500	600	13.9	48.5	17.0	100	3.2	2C	High temperature
13		IFR18650	1500	18.0	65.0	42.0	70	3.2	2C	
14		IFR26650	3200	26.0	65.0	85.0	30	3.2	2C	
15	3.7V	ICR10440	300	10.0	43.0	9.0	70	3.7	2C	
16		ICR14280	300	14.0	28.0	31.0	60	3.7	2C	
17		ICR14430	700	13.9	42.5	20.0	85	3.7	2C	
18		ICR14500	800	13.9	48.5	23.0	80	3.7	2C	
19		ICR14650	1100	13.9	65.0	30.0	75	3.7	2C	
20		ICR16340	600	16.0	34.0	17.0	110	3.7	2C	
21		ICR17500	1100	17.0	49.4	26.0	70	3.7	2C	
22		ICR17650	1250	16.6	65.0	38.0	60	3.7	2C	
23		ICR18350	1000	18.1	35.0	24.0	70	3.7	2C	
24		ICR18490	1300	18.1	49.0	33.0	80	3.7	2C	
25		ICR18500	1400	18.1	49.5	35.0	80	3.7	2C	
26		ICR18650	2200	18.1	65.0	45.0	70	3.7	2C	
27		ICR18650	2600	18.1	65.0	48.0	70	3.7	2C	
28		ICR22430	2000	22.0	42.5	45.0	60	3.7	2C	
29		ICR22650	3000	22.0	65.0	80.0	30	3.7	2C	
30		ICR26500	3200	26.0	49.5	90.0	20	3.7	2C	
31		ICR26650	4500	26.0	65.0	100.0	20	3.7	2C	
32		ICR17500	900	17.0	49.4	26.0	20	3.7	15C	High rate
33		ICR18500	1100	18.4	49.4	31.0	20	3.7	15C	
34		ICR18650	1500	18.4	65.4	41.0	25	3.7	10C	
35		ICR18650	1500	18.4	65.4	41.0	20	3.7	15C	
36		ICR26650	3000	26.2	65.6	85.0	20	3.7	15C	

E-mail: jayant2009@163.com;
Website: <http://www.goldenbattery.com.cn>

Tel: (+86) 755-89694987, (+86) 13682685008
Skype: richardliu2013