

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
1	57	12	25	100	≤5.7	12.2±0.5	≤25.5	15C	140	3.0	3.7
2	64	12	30	150	≤6.40	12±0.50	≤31	15C	100	4.0	3.7
3	57	12	35	180	≤5.7	12±0.5	≤36	10C	100	5.0	3.7
4	57	12	35	160	≤5.7	12±0.5	≤36	15C	100	5.0	3.7
5	64	12	47	280	≤6.50	12.0±0.50	≤48.50	10C	100	9.0	3.7
6	80	18	62	400	≤8.10	18±0.50	≤63.5	20C	80	14.0	3.7
7	43	20	25	150	≤4.40	20.0±0.50	≤25.50	10C	120	5.0	3.7
8	30	20	30	110	≤3.10	20±0.5	≤31	20C	120	4.0	3.7
9	47	20	30	180	≤4.80	20±0.5	≤31	20C	100	5.0	3.7
10	57	20	30	200	≤5.80	20.0±0.50	≤31.50	20C	80	6.5	3.7
11	57	20	30	200	≤5.7	20±0.50	≤31	20C	80	6.0	3.7
12	60	20	30	230	≤6.1	20.0±0.5	≤31.0	20C	80	7	3.7
13	67	20	30	260	≤6.70	20.0±0.50	≤31	20C	80	8.0	3.7
14	74	20	30	300	≤7.40	20±0.50	≤31.5	15C	80	8.0	3.7
15	74	20	30	300	≤7.50	20±0.5	≤31.5	20C	80	8.0	3.7
16	60	20	35	300	≤6.0	20±0.50	≤36	10C	80	8.0	3.7
17	74	20	35	380	≤7.50	20.0±0.50	≤37.00	15C	100	11.0	3.7
18	77	20	35	380	≤7.80	20.0±0.5	≤37.0	20C	80	10	3.7
19	57	20	40	300	≤5.80	20.0±0.50	≤41.50	20C	70	9.5	3.7
20	74	20	40	400	≤7.40	20.0±0.50	≤41.00	20C	50	12.0	3.7
21	50	20	45	330	≤5.00	19.8±0.50	≤45.5	5C	80	9.0	3.7
22	43	22	48	300	≤4.40	22.0±0.50	≤48.50	20C	35	9.5	3.7
23	64	22	48	500	≤6.50	22±0.50	≤49.50	20C	30	15.0	3.7
24	64	22	65	800	≤6.5	22±0.5	≤66.5	10C	40	20.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
25	60	24	64	750	≤6.10	24.0±0.5	≤65.0	20C	20	19	3.7
26	64	24	64	750	≤6.40	24.0±0.50	≤65.0	20C	15	20	3.7
27	84	25	29	400	≤8.40	25.0±0.5	≤31.0	20C	60	11	3.7
28	50	25	30	240	≤5.10	25±0.50	≤31	20C	80	7.0	3.7
29	80	27	95	2000	≤8.10	27±0.5	≤97.0	5C	20	45	3.7
30	84	27	95	2000	≤8.60	27.0±0.50	≤97.00	10C	20	46.0	3.7
31	36	30	48	450	≤3.60	30.0±0.50	≤48.50	5C	40	11.5	3.7
32	40	30	48	350	≤4.00	30±0.50	≤49	30C	30	12.0	3.7
33	43	30	48	450	≤4.30	30.0±0.50	≤48.50	20C	30	12.5	3.7
34	43	30	48	450	≤4.50	30±0.50	≤49.0	20C	25	13.0	3.7
35	44	30	48	470	≤4.50	30.0±0.5	≤49.5	25C	25	14	3.7
36	47	30	48	500	≤4.80	30±0.50	≤49	20C	25	14.5	3.7
37	47	30	48	400	≤4.70	30.0±0.50	≤49.00	30C	20	13.5	3.7
38	47	30	48	450	≤4.80	30.0±0.50	≤49	30C	30	13.5	3.7
39	50	30	48	600	≤5.10	30±0.50	≤49.0	10C	30	15	3.7
40	50	30	48	450	≤5.00	30±0.50	≤49.0	30C	30	14.5	3.7
41	57	30	48	700	≤5.80	30.0±0.50	≤49.50	10C	40	19.0	3.7
42	57	30	48	600	≤5.70	30.0±0.50	≤49.00	15C	30	16.0	3.7
43	60	30	48	750	≤6.10	30.0±0.50	≤49.50	10C	30	18.0	3.7
44	64	30	48	800	≤6.5	30.0±0.5	≤49.5	10C	30	19	3.7
45	64	30	48	700	≤6.50	30.0±0.5	≤49.5	15C	30	18	3.7
46	67	30	48	850	≤6.7	30±0.50	≤49	5C	30	20.0	3.7
47	70	30	48	800	≤7.1	30±0.50	≤49.5	10C	30	20	3.7
48	74	30	48	900	≤7.40	30.0±0.50	≤49.50	10C	30	23.0	3.7
49	74	30	48	800	≤7.40	30±0.50	≤49.50	20C	25	21.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
50	74	30	48	750	≤7.40	30±0.50	≤50	20C	20	21.0	3.7
51	77	30	48	950	≤7.80	30.0±0.50	≤50.0	10C	30	22.0	3.7
52	77	30	48	700	≤7.80	30.0±0.50	≤50.0	30C	25	22.0	3.7
53	80	30	48	900	≤8.00	30.0±0.50	≤50	15C	30	24.0	3.7
54	80	30	48	800	≤8.10	30±0.50	≤50	25C	20	23.0	3.7
55	80	30	48	800	≤8.10	30.0±0.50	≤50.0	30C	20	22.5	3.7
56	84	30	48	800	≤8.50	30.0±0.50	≤50	30C	20	24.0	3.7
57	87	30	48	800	≤8.80	30±0.50	≤50	35C	20	24.0	3.7
58	97	30	48	1000	≤10.00	30.5±0.50	≤50.50	30C	20	27.0	3.7
59	74	30	65	1300	≤7.50	30.0±0.50	≤67.00	10C	25	30.0	3.7
60	77	30	65	1300	≤7.80	30±0.50	≤67	15C	25	32.0	3.7
61	70	30	80	1500	≤7.1	30.0±0.5	≤81.0	10C	15	35	3.7
62	64	30	89	1550	≤6.40	30.0±0.50	≤90.00	10C	20	38.0	3.7
63	70	33	65	1300	≤7.10	33.0±0.3	≤66.5	20C	25	32	3.7
64	60	34	50	900	≤6.10	34±0.50	≤51.5	5C	25	20	3.7
65	47	34	56	900	≤4.80	34.0±0.5	≤57.0	5C	40	18	3.7
66	57	34	65	1100	≤5.80	34.0±0.50	≤66.00	10C	20	27.0	3.7
67	60	34	65	1200	≤6.1	34±0.50	≤66	10C	20	29.0	3.7
68	60	34	65	1000	≤6.10	34±0.50	≤66	30C	20	27.0	3.7
69	74	34	65	1300	≤7.40	34±0.50	≤66.5	20C	25	33.0	3.7
70	77	34	65	1300	≤7.80	34±0.50	≤66.5	30C	20	35.0	3.7
71	70	34	79	1600	≤7.10	34.0±0.5	≤80.0	20C	20	40	3.7
72	80	34	79	1800	≤8.10	34±0.50	≤79	15C	20	44.0	3.7
73	70	34	82	1800	≤7.20	34.0±0.50	≤84.00	10C	20	42.0	3.7
74	77	34	82	1800	≤7.80	34.0±0.50	≤84.00	15C	15	45.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
75	80	34	82	1800	≤8.10	34.0±0.50	≤84.50	20C	15	44.0	3.7
76	84	34	82	1800	≤8.50	34.3±0.50	≤84.50	30C	10	46.0	3.7
77	87	34	82	2000	≤8.70	34.0±0.50	≤84.00	15C	15	49.0	3.7
78	90	34	82	2300	≤9.00	34.0±0.50	≤84.50	10C	15	53.0	3.7
79	90	34	82	1800	≤9.20	34.0±0.50	≤84.50	30C	10	53.0	3.7
80	64	34	89	1750	≤6.40	34±0.50	≤90	10C	20	40.0	3.7
81	40	34	95	1100	≤4.10	34.0±0.50	≤96.00	5C	30	27.0	3.7
82	47	34	95	1300	≤4.80	34±0.5	≤96	5C	30	31.0	3.7
83	50	34	95	1500	≤5.10	34.0±0.5	≤96.0	15C	15	36	3.7
84	54	34	95	1700	≤5.5	34±0.50	≤96.50	10C	20	39	3.7
85	60	34	95	1800	≤6.10	34.0±0.5	≤96.5	5C	20	41	3.7
86	60	34	95	1900	≤6.10	34.0±0.50	≤96.5	10C	15	43.0	3.7
87	60	34	95	1500	≤6.10	34.0±0.50	≤96.0	20C	15	39.0	3.7
88	64	34	95	2100	≤6.50	34.0±0.50	≤96.50	5C	20	48.0	3.7
89	64	34	95	1600	≤6.40	34.0±0.50	≤96.5	20C	20	40.0	3.7
90	67	34	95	1600	≤6.70	34±0.50	≤96.5	30C	15	43.0	3.7
91	70	34	95	2100	≤7.20	34.5±0.50	≤97.50	10C	20	49.0	3.7
92	70	34	95	2000	≤7.20	34±0.5	≤96	15C	20	50.0	3.7
93	70	34	95	1800	≤7.0	34.0±0.50	≤96.5	20C	15	45.0	3.7
94	70	34	95	1800	≤7.10	34±0.50	≤96.5	25C	15	48.0	3.7
95	74	34	95	2300	≤7.40	34±0.50	≤96.5	5C	20	49.0	3.7
96	74	34	95	1800	≤7.40	34±0.50	≤97	20C	15	48.0	3.7
97	77	34	95	2300	≤7.80	34±0.50	≤97	10C	20	53.0	3.7
98	77	34	95	2200	≤7.80	34.0±0.50	≤96.50	15C	20	52.0	3.7
99	80	34	95	2200	≤8.10	34±0.50	≤96.5	20C	10	52.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
100	80	34	95	2100	≤8.10	34.5±0.50	≤97	20C	10	55.0	3.7
101	80	34	95	1800	≤8.00	34.5±0.50	≤96.5	30C	10	48.0	3.7
102	82	34	95	2200	≤8.10	34.5±0.50	≤96.50	20C	10	56	3.7
103	84	34	95	2200	≤8.50	34.0±0.50	≤97.00	20C	15	56.0	3.7
104	84	34	95	2200	≤8.40	34.5±0.50	≤97	20C	10	56.0	3.7
105	84	34	95	2100	≤8.40	34.5±0.50	≤97	25C	10	55.0	3.7
106	84	34	95	2100	≤8.50	34.5±0.50	≤96.5	30C	10	55.0	3.7
107	84	34	95	1800	≤8.40	34±0.50	≤97	40C	8	52.0	3.7
108	87	34	95	2200	≤8.70	34.5±0.50	≤97	25C	10	58.0	3.7
109	87	34	95	2200	≤8.80	34.0±0.50	≤97	25C	8	56.0	3.7
110	87	34	95	2100	≤8.90	34.0±0.50	≤97.00	30C	10	59.0	3.7
111	90	34	95	2100	≤9.10	34±0.50	≤96.5	30C	8	61.0	3.7
112	90	34	95	2100	≤9.10	34.3±0.50	≤97	35C	8	61.0	3.7
113	97	34	95	2800	≤9.80	34.0±0.50	≤97.50	10C	20	63.0	3.7
114	97	34	95	2500	≤9.70	34.5±0.5	≤97.5	20C	8	63	3.7
115	97	34	95	2500	≤9.70	34.5±0.50	≤97.50	20C	10	64.0	3.7
116	97	34	95	2500	≤10.10	34.3±0.50	≤97.00	30C	10	65.0	3.7
117	97	34	95	2500	≤9.8	90±0.50	≤153	30C	8	66.0	3.7
118	97	34	95	2100	≤9.70	34.5±0.5	≤97	40C	8	62.0	3.7
119	54	35	62	1050	≤5.5	35±0.50	≤63	10C	25	25.0	3.7
120	60	35	62	1000	≤6.0	35±0.50	≤63	20C	25	27.0	3.7
121	64	35	62	1400	≤6.30	35.0±0.5	≤63.0	5C	20	29	3.7
122	64	35	62	1200	≤6.3	35.0±0.5	≤63.0	10C	20	30	3.7
123	72	35	62	1300	≤7.30	35.0±0.50	≤64.0	10C	15	32	3.7
124	74	35	62	1400	≤7.50	35.0±0.5	≤63.50	10C	25	32	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
125	77	35	62	1300	≤7.70	35±0.50	≤63.5	20C	25	34.0	3.7
126	36	35	64	450	≤3.60	35±0.5	≤65.5	40C	40	15.0	3.7
127	57	35	64	1000	≤5.70	35±0.50	≤66	20C	25	26.0	3.7
128	60	35	64	1000	≤6.10	35.0±0.50	≤66.00	20C	20	27.0	3.7
129	60	35	64	1000	≤6.0	35±0.50	≤66	25C	20	27.0	3.7
130	60	35	64	1000	≤6.1	35±0.50	≤66.5	30C	25	27	3.7
131	64	35	64	1300	≤6.5	35.0±0.50	≤66.0	10C	25	32	3.7
132	64	35	64	1100	≤6.40	35.0±0.50	≤66.00	15C	25	28.0	3.7
133	64	35	64	1000	≤6.40	35±0.50	≤65.5	20C	20	28.0	3.7
134	67	35	64	1200	≤6.7	35.0±0.50	≤65.5	15C	25	30	3.7
135	67	35	64	1000	≤6.80	35±0.50	≤65.5	30C	20	30.0	3.7
136	70	35	64	1400	≤7.10	35.0±0.50	≤66.00	10C	25	34.0	3.7
137	70	35	64	1200	≤7.10	35.0±0.50	≤66.00	20C	20	32.0	3.7
138	74	35	64	1500	≤7.50	35.0±0.5	≤66.0	10C	20	34	3.7
139	74	35	64	1350	≤7.40	35.0±0.50	≤66.0	15C	25	33.0	3.7
140	74	35	64	1300	≤7.50	35±0.5	≤66	20C	25	33.0	3.7
141	74	35	64	1200	≤7.50	35±0.50	≤65.5	25C	20	34.0	3.7
142	77	35	64	1500	≤7.80	35.0±0.50	≤66.00	10C	25	36.0	3.7
143	77	35	64	1300	≤7.70	35±0.50	≤66	25C	20	35.0	3.7
144	77	35	64	1300	≤7.80	35±0.50	≤66.5	30C	20	36	3.7
145	80	35	64	1500	≤8.20	35.0±0.50	≤66.00	15C	20	37.0	3.7
146	80	35	64	1300	≤8.00	35±0.50	≤66.00	20C	20	35.0	3.7
147	80	35	64	1300	≤8.10	35±0.50	≤66.00	25C	20	35.0	3.7
148	80	35	64	1200	≤8.00	35.0±0.50	≤66.00	30C	20	36.0	3.7
149	87	35	64	1450	≤9.00	35.0±0.50	≤66.00	30C	20	41.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
150	90	35	64	1500	≤9.00	35.0±0.50	≤66.00	20C	20	38.0	3.7
151	40	35	130	1600	≤4.10	35.0±0.50	≤130.5	5C	20	37.0	3.7
152	40	35	130	1500	≤4.10	35.0±0.50	≤130.5	10C	20	37.0	3.7
153	70	35	130	3000	≤7.10	35.0±0.50	≤132.00	10C	15	68.0	3.7
154	84	35	130	3200	≤8.50	35.0±0.50	≤132.00	20C	8	82.0	3.7
155	84	35	130	3000	≤8.50	35.5±0.50	≤132.5	30C	10	84.0	3.7
156	87	35	130	3200	≤8.80	35±0.5	≤132	20C	10	82.0	3.7
157	97	39	62	2000	≤9.80	39.5±0.5	≤65.0	15C	15	48	3.7
158	60	40	60	1300	≤6.20	40.0±0.50	≤61.50	10C	25	32.0	3.7
159	74	41	67	1800	≤7.40	41.0±0.50	≤68.50	10C	15	43.0	3.7
160	87	41	67	1800	≤8.0	41.0±0.5	≤69.0	15C	15	44.0	3.7
161	77	41	120	2500	≤7.80	41±0.5	≤121.50	40C	10	76.0	3.7
162	94	41	120	4100	≤9.6	41.0±0.50	≤123.0	20C	10	107.0	3.7
163	97	41	120	4300	≤10.20	41.0±0.50	≤123.0	20C	10	110.0	3.7
164	77	43	74	2300	≤7.80	43.0±0.5	≤76.5	5C	15	50	3.7
165	80	43	74	2300	≤8.10	43.0±0.50	≤76.00	10C	15	54.0	3.7
166	80	43	74	2200	≤8.10	43±0.50	≤75.50	15C	15	53.0	3.7
167	84	43	74	2200	≤8.50	43±0.5	≤76	20C	15	55.0	3.7
168	87	43	74	2300	≤8.70	43.0±0.50	≤76.00	15C	15	57.0	3.7
169	54	44	90	2000	≤5.50	44.0±0.5	≤91.5	5C	20	45	3.7
170	60	44	90	2100	≤6.10	44.0±0.50	≤91.5	10C	20	52.0	3.7
171	67	44	90	2500	≤6.80	44.0±0.50	≤92.00	10C	15	53.0	3.7
172	84	44	90	2500	≤8.40	44.0±0.50	≤92.00	30C	8	67.0	3.7
173	87	44	90	2500	≤8.80	44.0±0.50	≤92.50	30C	8	72.0	3.7
174	80	44	125	3300	≤8.10	44.0±0.50	≤125.5	30C	6	88	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
175	80	44	125	3500	≤8.10	44.0±0.5	≤125.5	30C	6	90	3.7
176	40	45	135	2000	≤4.00	45.0±0.50	≤137.0	20C	12	54.0	3.7
177	50	45	135	2500	≤5.10	45±0.5	≤136.0	20C	15	64	3.7
178	50	45	135	2500	≤5.10	45±0.50	≤135.5	20C	10	62.0	3.7
179	54	45	135	3000	≤5.40	45.0±0.50	≤136.50	10C	15	70.0	3.7
180	54	45	135	2650	≤5.5	45±0.50	≤136	20C	15	67.0	3.7
181	57	45	135	3000	≤5.80	45±0.50	≤136	20C	10	74.0	3.7
182	57	45	135	2500	≤5.80	45±0.50	≤136	30C	8	73.0	3.7
183	60	45	135	3200	≤6.0	45.0±0.5	≤136.5	15C	8	76	3.7
184	60	45	135	2650	≤6.0	45±0.50	≤136.50	30C	8	70.0	3.7
185	60	45	135	2500	≤6.10	45±0.50	≤136	35C	8	75.0	3.7
186	64	45	135	3300	≤6.50	45.0±0.50	≤137.0	20C	10	84.0	3.7
187	64	45	135	3300	≤6.50	45±0.50	≤136.50	20C	10	81.0	3.7
188	64	45	135	3000	≤6.50	45±0.50	≤136.50	30C	8	79.0	3.7
189	67	45	135	4000	≤6.90	45.0±0.50	≤137.00	10C	10	91.0	3.7
190	67	45	135	3300	≤6.80	45.0±0.50	≤137.0	20C	6	85.0	3.7
191	67	45	135	3000	≤6.80	45.0±0.50	≤137.00	25C	10	85.0	3.7
192	67	45	135	3000	≤6.80	45±0.50	≤136.50	35C	6	86.0	3.7
193	70	45	135	4000	≤7.10	45±0.50	≤137	10C	10	91.0	3.7
194	74	45	135	4000	≤7.50	45±0.50	≤137	15C	10	100.0	3.7
195	77	45	135	3500	≤7.80	45.0±0.50	≤137.0	30C	8	99.0	3.7
196	77	45	135	3500	≤7.9	45±0.50	≤137	30C	6	101.0	3.7
197	80	45	135	3200	≤8.00	45±0.5	≤136.50	40C	8	99.0	3.7
198	84	45	135	4000	≤8.40	45±0.50	≤137.50	20C	8	102	3.7
199	84	45	135	4000	≤8.40	45.0±0.50	≤137.00	25C	8	110.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
200	84	45	135	4000	≤8.50	45.0±0.50	≤137.50	30C	8	112.0	3.7
201	87	45	135	5000	≤8.70	45.0±0.50	≤137.0	10C	8	115.0	3.7
202	90	45	135	5000	≤9.00	45.0±0.50	≤137.50	15C	8	120.0	3.7
203	90	45	135	4000	≤9.10	45±0.5	≤137	30C	8	116.0	3.7
204	94	45	135	5000	≤9.50	45.3±0.50	≤137.50	15C	8	122.0	3.7
205	97	45	135	5000	≤9.70	45.5±0.50	≤137.50	20C	8	118.0	3.7
206	97	45	135	5000	≤9.70	45±0.50	≤137.50	20C	5	120.0	3.7
207	70	46	89	1600	≤7.10	45.5±0.5	≤89.0	15C	5	56	3.7
208	54	47	125	3000	≤5.50	47.0±0.50	≤126.50	10C	20	72.0	3.7
209	67	47	125	4000	≤6.80	47.0±0.50	≤127.00	5C	10	86.0	3.7
210	70	47	125	4200	≤7.1	47±0.5	≤127.0	5C	10	89	3.7
211	70	47	125	4000	≤7.20	47.0±0.50	≤127.00	10C	10	92.0	3.7
212	80	47	125	4300	≤8.00	47±0.50	≤127.5	10C	10	98.0	3.7
213	80	48	166	6400	≤8.10	48±0.5	≤168	5C	15	135.0	3.7
214	40	50	63	990	≤4.10	50.0±0.5	≤64	20C	20	25	3.7
215	50	50	63	1400	≤5.20	50.0±0.50	≤64.0	15C	20	35	3.7
216	77	50	100	2800	≤7.80	50.0±0.50	≤102.0	30C	6	75	3.7
217	50	50	140	2500	≤5.00	50±0.50	≤140.50	25C	10	69.0	3.7
218	50	50	140	2500	≤5.1	50±0.5	≤141.5	30C	7	72	3.7
219	57	50	140	3000	≤5.80	50.0±0.50	≤142.00	30C	8	87.0	3.7
220	60	50	140	4000	≤6.20	50.0±0.50	≤141.50	10C	6	92.0	3.7
221	60	50	140	3300	≤6.00	50±0.50	≤141.50	25C	8	86.0	3.7
222	64	50	140	3500	≤6.40	50±0.50	≤141.50	25C	10	94.0	3.7
223	64	50	140	3500	≤6.50	50±0.50	≤141.50	25C	8	92.0	3.7
224	64	50	140	3500	≤6.6	50.0±0.50	≤141.50	30C	7	98.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
225	67	50	140	4400	≤6.70	50±0.50	≤141	10C	10	99.0	3.7
226	67	50	140	4000	≤6.80	50.0±0.50	≤141.5	20C	10	103	3.7
227	70	50	140	4000	≤7.10	50±0.50	≤142	20C	10	103.0	3.7
228	70	50	140	4000	≤7.0	50±0.50	≤141.50	25C	8	102.0	3.7
229	70	50	140	4000	≤7.10	50.0±0.50	≤142.00	25C	8	108.0	3.7
230	74	50	140	4000	≤7.50	50±0.5	≤142	30C	6	107	3.7
231	80	50	140	4100	≤8.10	50±0.50	≤142.00	30C	7	121.0	3.7
232	94	50	140	5000	≤9.50	50.5±0.5	≤143	30C	5	131	3.7
233	64	50	150	5000	≤6.50	50±0.50	≤151.5	5C	10	105.0	3.7
234	67	50	150	5000	≤6.90	50.0±0.50	≤152.00	10C	8	114.0	3.7
235	74	50	150	5000	≤7.50	50.0±0.50	≤152.00	15C	10	118.0	3.7
236	80	50	150	5000	≤8.10	50.0±0.50	≤153.00	20C	8	129.0	3.7
237	80	50	150	5000	≤8.10	50.0±0.50	≤152.50	20C	8	128.0	3.7
238	84	50	150	6000	≤8.50	50.0±0.50	≤152.00	10C	10	138.0	3.7
239	84	50	150	5000	≤8.40	50.0±0.50	≤152.50	25C	8	138.0	3.7
240	54	51	72	1800	≤5.5	51±0.50	≤73	10C	25	43.0	3.7
241	74	55	168	5000	≤7.50	55.0±0.50	≤168.0	30C	5	140.0	3.7
242	74	58	90	3500	≤7.50	58.0±0.50	≤90	10C	15	80.0	3.7
243	50	59	156	4000	≤5.10	59±0.50	≤158	15C	8	100	3.7
244	56	59	156	5200	≤5.60	59.0±0.5	≤158.50	5C	8	110	3.7
245	60	59	156	4500	≤6.00	59.0±0.50	≤157	30C	8	119.0	3.7
246	67	59	156	5000	≤6.80	59.5±0.50	≤158.0	25C	8	135.0	3.7
247	67	59	156	4500	≤6.80	59.50±0.50	≤158.0	30C	8	127.0	3.7
248	67	59	156	5000	≤6.80	59.0±0.50	≤157.50	30C	8	134.0	3.7
249	67	59	156	4200	≤6.80	59.5±0.5	≤158.50	40C	8	126.0	3.7

深圳市金池能源科技有限公司
Shenzhen Goldenbattery Technology Co., Ltd.

高倍率锂离子电池产品规格表/ High rate Li-ion battery product specification

No.	Product type			Nominal capacity (mAh)	Size (mm)			Discharge rate	IR (mΩ)	Weight (g)	Nominal Voltage (V)
					Thickness	Width	Length				
250	70	59	156	5000	≤7.10	59.5±0.5	≤158	25C	8	133.0	3.7
251	70	59	156	5000	≤7.10	59.5±0.50	≤158	25C	6	132.0	3.7
252	77	59	156	5000	≤7.70	59±0.50	≤158.0	30C	6	150.0	3.7
253	80	59	156	8000	≤8.10	59.0±0.50	≤158.50	5C	10	165.0	3.7
254	80	59	156	7200	≤8.10	59.5±0.50	≤159.0	10C	5	162.0	3.7
255	84	59	156	8000	≤8.50	59.5±0.50	≤159.0	5C	5	172	3.7
256	90	59	156	8000	≤9.10	59.0±0.50	≤159.00	10C	10	175.0	3.7
257	94	59	156	8000	≤9.50	59.5±0.50	≤159.5	15C	8	185.0	3.7
258	97	59	156	10000	≤10.30	59.5±0.50	≤159.00	5C	5	214.0	3.7
259	99	59	156	9400	≤10.3	59.5±0.50	≤159.5	10C	5	210.0	3.7
260	99	59	156	8600	≤10.00	59.5±0.50	≤159.5	15C	5	197.0	3.7
261	94	60	260	15000	≤9.50	60.5±0.5	≤261.0	5C	8	315	3.7
262	57	61	66	2000	≤5.80	61.5±0.50	≤67	10C	15	45.0	3.7
263	70	61	93	4100	≤7.10	61±0.50	≤94	5C	15	85.0	3.7
264	94	61	93	5500	≤9.50	61±0.50	≤96	5C	10	115.0	3.7
265	40	64	69	1300	≤4.00	64±0.50	≤69.50	10C	20	32.0	3.7
266	50	64	69	2000	≤5.10	64.0±0.50	≤70.00	10C	15	46.0	3.7
267	54	64	69	2200	≤5.50	64.0±0.50	≤70.00	10C	20	52.0	3.7
268	57	64	69	2200	≤5.80	64±0.50	≤70	15C	20	54.0	3.7
269	60	64	69	2400	≤6.10	64.0±0.50	≤70.50	10C	15	57.0	3.7
270	84	67	100	4500	≤8.40	67.0±0.50	≤103.0	25C	5	126	3.7
271	90	67	100	5000	≤9.20	67.0±0.50	≤103.5	20C	5	126	3.7
272	84	67	130	6600	≤8.5	67±0.50	≤132.5	20C	5	158	3.7
273	54	70	76	2600	≤5.50	70.0±0.50	≤77.50	10C	20	62.0	3.7
274	54	70	171	6000	≤5.5	70.0±0.5	≤172.0	5C	8	133	3.7

